

Hammond Watertight Diecast Aluminium Boxes - Flanged Lid — 1590W “FL” Series

Rugged, diecast aluminium alloy . Tough yet easy to machine. Meets IP65.

- Lap joint construction with a factory poured of silicone rubber around the perimeter provides protection against dust & splashing water. Silicone gasket remains flexible from -62 to $+232^{\circ}\text{C}$.
- Painted version is painted with tough polyester powder paint for lasting finish.
- Assembled with 6-32 x 1/2” stainless steel colour matched machine screws & ‘O’ rings.
- Flanged lid allows for easy mounting to walls or shelves & provides high security.



Approx Draft = $1^{\circ}15'$ to 2°

For detailed drawings and CAD files visit ww.hammondmfg.com

Part Number		Length	Width	Height (no lid)	Height With Lid
Unpainted	Black				
26-1590WLBFL	26-1590WLBFLBK	51	51	27	31
26-1590WAFL	26-1590WAFLBK	93	39	27	31
26-1590WGFL	26-1590WGFLBK	100	50	21	25
26-1590WSFL	26-1590WSFLBK	111	82	40	44
26-1590WBFL	26-1590WBFLBK	112	60	27	31
26-1590WBBFL	26-1590WBBFLBK	119	94	30	34
26-1590WQFL	26-1590WQFLBK	120	120	28	32
26-1590WUFL	26-1590WUFLBK	120	120	55	59
26-1590WVFL	26-1590WVFLBK	120	120	90	94
26-1590WCFL	26-1590WCFLBK	120	94	53	56.5
26-1590WTFL	26-1590WTFLBK	121	80	55	59
26-1590WN1FL	26-1590WN1FLBK	121.1	66	35.3	39.3
26-1590WP1FL	26-1590WP1FLBK	153	82	46	50
26-1590WDDFL	26-1590WDDFLBK	188	119.5	33	37
26-1590WDFL	26-1590WDFLBK	188	120	52	56
26-1590WEFL	26-1590WEFLBK	188	120	78	82
26-1590WFFL	26-1590WFFLBK	188	188	63	67
26-1590WR1FL	26-1590WR1FLBK	192	111	57	61